

YAV2CL2TC38FX, Cu Compression, 2-Hole, 3/8" Stud, 1" Spacing, Standard Barrel, 2 Flex

By Burndy

Catalog # [YAV2CL2TC38FX](#)

2 Flex G,H,I,K,M,DLO, 2 AWG, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Standard Barrel, Inspection Window



Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2 AWG
Conductor - Copper Str Size	"2 AWG"
Conductor - Copper Flex I Size Range	2 AWG
Conductor - Copper Flex K Size	"2 AWG"
Conductor - Copper Flex K Size Range	2 AWG
Conductor - Copper Flex M Size	"2 AWG"
Conductor - Copper Solid Size	2 AWG
Conductor - Copper Str Compact Size	"2 AWG"
Conductor - Copper DLO Size	2 AWG
Conductor - Copper DLO Size Range	2 AWG
Conductor - Copper Flex G Size	"2 AWG"
Conductor - Copper Str Navy Size	60
Conductor - Copper Flex G Size Range	2 AWG

Conductor - Copper Str Navy Size Range	60 (37) Navy
Conductor - Copper Flex H Size	"2 AWG"
Conductor Size	2 AWG
Conductor - Copper Str Size Range	2 AWG
Conductor - Copper Flex H Size Range	2 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"2 AWG"
Conductor - CopperWeld Str Size	2 A AWG;2 F AWG;2 G AWG;2 J AWG;2 K AWG;2 N AWG;2 P AWG

Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.46 in
Dimension - L Length Overall mm	72 mm
Dimension - Pad Width inch	0.68 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	11/16
Dimension - Stud Size fraction	3/8
Dimension - B Length fraction	5/8 in
Dimension - B Length inch	0.63 in
Dimension - Z inch	0.43 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	2.82 in

Dimension - N inch 0.41 in

General

Die Index 10
Trade Name HYLUG™
Sub Brand HYLUG
Color Code Brown
Physical Attribute - Tongue Standard
Type
Plated Y
Feature - Barrel Type Standard
Feature - Barrel Style Chamfered
Type Standard Barrel, Tin Plated
UPC 12 Digit 781810022245

UPC 14 Digit GTIN 00781810022245
Material COPPER
Plating Type Tin - Electro Plated
Finish Type Tin-Plated
UPC 781810022245

Logistics

Minimum Pack Quantity 1
Carton Quantity 25

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)
[Installation Manual \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YAV2CL2TC38FX-SPEC-EN | REV 11/2025