

## YAV4CLTC14FX, Compression Terminal, 4 Flex G,H,I,K,M, DLO, 4 AWG, Cu, 1-Hole, 1/4" Stud, Standard Barrel

By Burndy  
Catalog # [YAV4CLTC14FX](#)

4 Flex G,H,I,K,M,DLO, 4 AWG, CU, 1 Hole, 1/4 Stud, Standard Barrel, Inspection Window



### Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

### Application

Wire Termination

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - CSA Approved	Yes

### Conductor

Conductor - Material	COPPER
Wire Size	4 AWG
Conductor - Copper Str Size	"4 AWG"
Conductor - Copper Flex I Size Range	4 AWG
Conductor - Copper Flex K Size	"4 AWG"
Conductor - Copper Flex K Size Range	4 AWG
Conductor - Copper Flex M Size	"4 AWG"
Conductor - Copper Flex M Size Range	4 AWG
Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Compact Size	"4 AWG"
Conductor - Copper DLO Size	4 AWG
Conductor - Copper DLO Size Range	4 AWG
Conductor - Copper Flex G Size	"4 AWG"
Conductor - Copper Str Navy Size	40
Conductor - Copper Flex G Size Range	4 AWG

Conductor - Copper Str Navy Size Range	40 (19) Navy-50 (19) Navy
Conductor - Copper Flex H Size	"4 AWG"
Conductor Size	4 AWG
Conductor - Copper Str Size Range	4 AWG
Conductor - Copper Flex H Size Range	4 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"4 AWG"
Conductor - CopperWeld Str Size	4 A AWG;4 D AWG;4 N AWG;4 P AWG
Conductor - CopperWeld Str Size Range	4 A AWG-4 P AWG

### Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - Outside Diameter inch	0.38 in
Dimension - L Length Overall mm	37 mm
Dimension - Pad Width inch	0.55 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	1/2
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4
Dimension - B Length fraction	1/2 in
Dimension - B Length inch	0.50 in
Dimension - Z inch	0.33 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25

Dimension - Length Overall  
inch 1.44 in  
Dimension - D inch 0.64 in  
Dimension - N inch 0.31 in

### General

Die Index 8  
Trade Name HYLUG™  
Sub Brand HYLUG  
Color Code Gray  
Physical Attribute - Tongue  
Type Standard  
Plated Y  
Feature - Barrel Type Standard  
Feature - Barrel Style Chamfered  
Type Standard Barrel, Tin Plated  
UPC 12 Digit 781810022573

UPC 14 Digit GTIN 00781810022573  
Material COPPER  
Plating Type Tin - Electro Plated  
Finish Type Tin-Plated  
UPC 781810022573

### Logistics

Minimum Pack Quantity 1  
Carton Quantity 50

### Operational

Temperature Rating 194

### Product Assets

[Catalog \[English\]](#)  
[Installation Manual \[English\]](#)  
[Installation Manual \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved  
BRDY-YAV4CLTC14FX-SPEC-EN | REV 11/2025