



YAV4CLTC38FX, Compression Terminal, 4 Flex G,H,I,K,M, DLO, 4 AWG, Cu, 1-Hole, 3/8" Stud, Standard Barrel

By Burndy

Catalog # [YAV4CLTC38FX](#)

4 Flex G,H,I,K,M,DLO, 4 AWG, CU, 1 Hole, 3/8 Stud, Standard Barrel, Inspection Window

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	4 AWG
Conductor - Copper Str Size	"4 AWG"
Conductor - Copper Flex I Size	4 AWG
Range	
Conductor - Copper Flex K Size	"4 AWG"
Conductor - Copper Flex K Size	4 AWG
Range	
Conductor - Copper Flex M Size	"4 AWG"
Conductor - Copper Flex M Size	4 AWG
Range	
Conductor - Copper Solid Size	4 AWG
Conductor - Copper Str	"4 AWG"
Compact Size	
Conductor - Copper DLO Size	4 AWG
Conductor - Copper DLO Size	4 AWG
Range	
Conductor - Copper Flex G Size	"4 AWG"
Conductor - Copper Str Navy	40
Size	



Conductor - Copper Flex G Size	4 AWG
Range	
Conductor - Copper Str Navy	40 (19) Navy-50 (19) Navy
Size Range	
Conductor - Copper Flex H Size	"4 AWG"
Conductor Size	4 AWG
Conductor - Copper Str Size	4 AWG
Range	
Conductor - Copper Flex H Size	4 AWG
Range	
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"4 AWG"
Conductor - CopperWeld Str	4 A AWG;4 D AWG;4 N AWG;4
Size	P AWG
Conductor - CopperWeld Str	4 A AWG-4 P AWG
Size Range	

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.38 in
Dimension - L Length Overall mm	42 mm
Dimension - Pad Width inch	0.58 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1/2
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - B Length fraction	1/2 in
Dimension - B Length inch	0.50 in
Dimension - Z inch	0.42 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in

Dimension - Bolt Size fraction	3/8	Type	Standard Barrel, Tin Plated
Dimension - Bolt Size inch	0.38	UPC 12 Digit	781810022627
Dimension - Length Overall	1.67 in	UPC 14 Digit GTIN	00781810022627
inch		Material	COPPER
Dimension - D inch	0.83 in	Plating Type	Tin - Electro Plated
Dimension - N inch	0.41 in	Finish Type	Tin-Plated
		UPC	781810022627
General		Logistics	
Die Index	8	Minimum Pack Quantity	1
Trade Name	HYLUG™	Carton Quantity	50
Sub Brand	HYLUG		
Color Code	Gray	Product Assets	
Physical Attribute - Tongue	Standard	Catalog [English]	
Type		Installation Manual [English]	
Plated	Y	Installation Manual [English]	
Feature - Barrel Type	Standard		
Feature - Barrel Style	Chamfered		



A Hubbell brand