


YAV9CL36BOX, Uninsulated Ring Terminal For 10 - 9 AWG

By Burndy
Catalog # [YAV9CL36BOX](#)



Seamless Uninsulated Compression Heavy Duty Ring Tongue Terminal, 10-9 Str., 8-10, .97 in L, .31 in W.

Features

- Manufactured from seamless pure electrolytic copper tubing to provide maximum conductivity, low resistance and excellent ductility for crimping
- Seamless tubular crimp barrel design - No seams to split resulting in a very high quality electrical connection, also can be used on solid conductor
- Double thick tongue structurally a very strong terminal tongue
- Produced from tubular copper, extra copper material assures the compression connector will operate cooler than the conductors it connects
- Internally bevelled barrel for easy cable entry, especially for flexible conductors
- Inspection hole provides easy visual check for proper conductor insertion
- Electro-tin plated for a long lasting durable corrosion resistance

Application

For Use On Copper Commercial (Code) Cable, Type AN Aircraft Cable And Extra Flexible Conductors, Industrials, Hospitals, Electric Utilities, Shipboard And Marine, Computers, Steel Mills, Mining Equipment And Other Equipment That Is Subject To Vibration Or Requiring Dependable Electrical Performance

General

Catalog Number	YAV9CL36BOX
Connector Type	Ring Terminal
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Copper
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYLUG
Trade Name	HYLUG™
Type	Ring Tongue
UPC	781810541586

UPC 14 Digit GTIN

00781810541586

Dimensions

Dimension - B Length fraction	2/5 in
Dimension - B Length inch	0.39 in
Dimension - Bolt Size fraction	#8 - #10
Dimension - D inch	0.36 in
Dimension - Hole Size fraction	1/5
Dimension - Hole Size inch	0.19 in
Dimension - L Length Overall mm	24 mm
Dimension - Length Overall inch	0.94 in
Dimension - N inch	0.16 in
Dimension - Outside Diameter inch	0.23 in
Dimension - Pad Width inch	0.31 in
Dimension - Strip Length inch	7/16 in
Dimension - Stud Size inch	#8;#10
Dimension - Z (inch)	0.15 in

Conductor Related

Conductor - Copper Str Navy Size	9 (7) Navy;9 (37) Navy;14 (7) Navy;14 (140) Navy
Conductor - Copper Str Navy Size Range	9 (7) Navy-14 (140) Navy
Conductor - Copper Str Size	10 AWG;9 AWG
Conductor - Copper Str Size Range	10 AWG - 9 AWG
Conductor Size	10 - 9 AWG
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Size • CU C Str Aircraft-Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM

UL Listed Yes

Logistics

Carton Quantity 600
Minimum Pack Quantity 50
Pallet Quantity 99999

[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_YAV10L36BOX_LineArt](#)
[Sales Drawings - 50094160](#)
[Specifications - YAV9CL36BOX](#)

Product Assets



©2025 Hubbell Incorporated. All rights reserved
BRDY-YAV9CL36BOX-SPEC-EN | REV 7/2025