

YAZ4C2N, Cu Compression, 2-Hole, 1/2" Stud, 1-3/4" Spacing, Long Barrel, 4 AWG

By Burndy
Catalog # [YAZ4C2N](#)

4 AWG, CU, 2 Hole, 1/2 Stud, 1-3/4 IN Spacing, Long Barrel, Inspection Window



Features

- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damaging of the strands
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

Specifications

| | |
|------------------------------------|--------------|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | UL 486A-486B |
| Certification - ETL | No |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | Yes |
| UL Listed | Yes |

Conductor

| | |
|----------------------------------|--------------|
| Conductor - Material | COPPER |
| Conductor - Copper Str Size | 4 AWG |
| Conductor - Copper Str Navy Size | 40 (19) Navy |
| Conductor Size | 4 AWG |
| Conductor Type | CODE |

Configuration

| | |
|--------------------------------------|-------------|
| Physical Attribute - Number of Holes | 2 |
| Connector Type | LONG BARREL |

Current

| | |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating | 35 kV |

Dimensions

| | |
|-----------------------------------|----------|
| Dimension - Outside Diameter inch | 0.34 in |
| Dimension - L Length Overall mm | 113 mm |
| Dimension - Pad Width inch | 0.83 in |
| Dimension - Hole Size fraction | 1/2 |
| Dimension - Hole Size inch | 0.56 |
| Dimension - Hole Size mm | 14 mm |
| Dimension - Strip Length inch | 1-3/16 |
| Dimension - Stud Size fraction | 1/2 |
| Dimension - Stud Size inch | 1/2 |
| Dimension - B Length fraction | 1-1/8 in |
| Dimension - B Length inch | 1.12 in |
| Dimension - Z inch | 0.64 in |
| Physical Attribute - Tongue Angle | Straight |
| Dimension - Bolt Hole Size inch | 0.52 in |
| Dimension - Bolt Size fraction | 1/2 |
| Dimension - Bolt Size inch | 0.5 |
| Dimension - Length Overall inch | 4.45 in |
| Dimension - N inch | 0.62 in |

General

| | |
|------------------------|--------------------------------|
| Die Index | 8 |
| Trade Name | HYLUG™ |
| Sub Brand | HYLUG |
| Color Code | Gray |
| Plated | Y |
| Feature - Barrel Type | Long |
| Feature - Barrel Style | Skived |
| Type | Long Barrel, Skive, Tin Plated |
| UPC 12 Digit | 781810208540 |
| UPC 14 Digit GTIN | 00781810208540 |
| Material | COPPER |
| Plating Type | Tin - Electro Plated |
| Finish Type | Tin-Plated |
| UPC | 781810208540 |

Logistics

| | |
|-----------------------|----|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 50 |

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)

[Installation Manual \[French, English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YAZ4C2N-SPEC-EN | REV 11/2025