

YC28C26, Copper C-Shape Connector

By Burndy
Catalog # YC28C26



CU Compression C Shape Compression Connector, 600 Volts to 35 kV, Run: 3/0 Str. - 4/0 Str., Tap: 1/0 Str. - 2/0 Str.

Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A;UL486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL 486A;UL486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Tap Range	1/0 AWG-2/0 AWG

Dimensions

Dimension - L Length Overall mm	27 mm
Dimension - Height inch	1.61 in
Dimension - Height mm	0 mm
Dimension - Length Overall inch	1.07 in

General

Die Index	F or D3
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Plated	N
Type	YC-C Series
UPC 12 Digit	781810116005
UPC 14 Digit GTIN	00781810116005
Material	Copper
Plating Type	Unplated
UPC	781810116005

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	5800

Product Assets

[Catalog \[English\]](#)