



YC3L12

by Burndy
Catalog ID: YC3L12

Prop65

Copper Compression C Tap, Thin Wall, 5-4 AWG (Run), 6-5 AWG (Tap).

Features: Manufactured Form High Conductivity Wrought Copper: Provides Low Resistance And Excellent Electrical Conductivity, Range-Taking Connector: Lowers Inventory Requirements, Reinforced Ribs: Provides Maximum Pull-Out Values, Compact Size: Easy To Tape And Insulate Connection, Economical: Provides Low Installed Cost, Use PUADP-1 Adapter With U Dies In Y46 HYPRESS, Color Code: Green, Wire Strip Length: 1-3/16 IN, Die Index: 11 Element A, Shape: C, Number Of Ribs: 1, Tools, Die Set Catalog Number, And (number Of Crimps): Mechanical: MD6, OUR840, MD7-34R, Y2MR Tool, W1CVT Die, (2)

Product Details

General

Application	For Making Copper Tap And Parallel Connections
Color Code	Green
Connector Type	C-Tap
Die Index	11
Item Type	3A
Material	Copper
Plated	Y
Plating Type	Tin - Bright
Sub Brand	CRIMPIT
Temperature Rating	194
Type	YC-L Series
UPC	781810040140
UPC 12 Digit	7818100401400

Dimensions

Dimension - B Length fraction	7/16 in
Dimension - B Length inch	0.46 in
Dimension - D inch	1.18 in
Dimension - Pad Width inch	0.27 in
Dimension - Strip Length inch	1-3/16

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper Str Run	5 AWG;4 AWG;3 AWG
----------------------------	-------------------

Conductor - Copper Str Run Range	5 AWG-3 AWG
Conductor - Copper Str Tap	12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG
Conductor - Copper Str Tap Range	12 AWG-5 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)