

YC4C4, Copper C-Shape Connector

By Burndy
Catalog # YC4C4

CU Compression C Shape Compression Connector, 600 Volts to 35 kV, 6 Sol. - 4 Str. (Run & Tap)



Features

- Range-taking connector lowering inventory requirements
- Compact size, easy to tape and insulate connection
- High conductivity wrought copper provides low resistance and excellent electrical conductivity

Application

For Range Of Copper And Making Tap Or Parallel Copper Connections

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A;UL486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A;UL486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Copper Solid Run Range	6 Sol. - 4 Str.
Conductor - Copper Solid Tap Range	6 Sol. - 4 Str.
Conductor - Copper Str Run Range	6 Sol. - 4 Str.

Conductor - Copper Str Tap	4 AWG
Conductor Type	Cu C Sol-Size

Dimensions

Dimension - L Length Overall mm	14 mm
Dimension - Height inch	0.81 in
Dimension - Height mm	0 mm
Dimension - Length Overall inch	0.57 in

General

Die Index	BG or 5/8
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Plated	N
Type	YC-C Series
UPC 12 Digit	781810113509
UPC 14 Digit GTIN	00781810113509
Material	Copper
Plating Type	Unplated
UPC	781810113509

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	57600

Product Assets

[Catalog \[English\]](#)