



YCAB394N

by Burndy
Catalog ID: YCAB394N

Prop 65 Notice

Copper compression lug designed for terminating copper conductors to switch pads and other substation switch yard apparatus, Die Index: 627.

Features: NEMA standard mounting holes, Made of pure copper.

Product Details

General

Application	Designed for terminating copper conductors to switch pads and other substation or switch yard apparatus
Connector Type	Terminal
Die Index	627
Material	Copper
Oxide Inhibitor Type	Penetrox A
Physical Attribute - Number of Crimps Required	2
Physical Attribute - Number of Holes	4
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINALS, HYLUG
Trade Name	HYLUG™
Type	YCAB-4N
UPC	781810014868

Dimensions

Dimension - B Length inch	3 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Hole Size fraction	14/25 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall mm	217 mm
Dimension - Length Overall inch	8.53 in
Dimension - N inch	0.62 in
Dimension - Outside Diameter inch	1.7 in
Dimension - Pad Width inch	3 in
Dimension - Strip Length inch	3 1/16
Dimension - Stud Size inch	33/64
Dimension - Z inch	0.63 in
Physical Attribute - Tongue Angle	Straight

Conductor Related

Conductor - Copper Str Size	750 kcmil
Conductor - Copper Str Size Range	750 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	5
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)