


## YCAB394N, Copper compression lug 4-Hole pad, 1/2" Stud, 1-3/4" Spacing. Used for terminating copper conductor to switch pads and other apparatus



By Burndy

Catalog # [YCAB394N](#)

Copper compression lug designed for terminating copper conductors to switch pads and other substation switch yard apparatus, Die Index: 627

### Features

- NEMA Standard mounting holes
- Made of pure copper

### Application

Designed for terminating copper conductors to switch pads and other substation or switch yard apparatus

### Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Buy America(n) Qualified	No
Certification - ETL	Contact Manufacturer
Standards - RoHS Compliance Status	No
Certification - CSA Approved	EX
UL Listed	No

### Conductor

Conductor - Copper Str Size	750 kcmil
Conductor - Copper Str Size Range	750 kcmil

### Configuration

Physical Attribute - Number of Crimps Required	2
Physical Attribute - Number of Holes	4
Connector Type	Terminal

### Dimensions

Dimension - F Width Center to Center inch	1.75 in
---	---------

Dimension - Outside Diameter inch	1.7 in
Dimension - L Length Overall mm	217 mm
Dimension - Pad Width inch	3 in
Dimension - Hole Size fraction	14/25 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Strip Length inch	3 1/16
Dimension - Stud Size inch	33/64
Dimension - B Length inch	3 in
Dimension - Z inch	0.63 in
Physical Attribute - Tongue Angle	Straight
Dimension - Length Overall inch	8.53 in
Dimension - N inch	0.62 in

### General

Die Index	627
Trade Name	HYLUG™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox A
Sub Brand	TERMINALS, HYLUG
Plated	N
Type	YCAB-4N
UPC 14 Digit GTIN	00781810014868
Material	Copper
Plating Type	Unplated
UPC	781810014868

### Logistics

Minimum Pack Quantity	5
Carton Quantity	1
Pallet Quantity	1

### Product Assets

[Catalog \[English\]](#)