



YCAK36A2G1, Al compression lug, Prefilled with PENETROX Oxide Inhibitor filled

By Burndy
Catalog # [YCAK36A2G1](#)



AL compression lug for joining AL and CU cable to transformer and equipment pads, Prefilled with PENETROX, 6.55 IN L.

General

Catalog Number	YCAK36A2G1
Die Index	608;786
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Physical Attribute - Tongue Type	Standard
Prefilled Oxide Inhibitor	Y
Trade Name	HYLUG™
UPC	781810810323
UPC 14 Digit GTIN	00781810810323

Dimensions

Dimension - B Length fraction	6-1/2 in
Dimension - D inch	3 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - Hole Size inch	0.56 in
Dimension - Pad Width inch	1.50 in
Physical Attribute - Tongue Angle	Straight

Conductor Related

Conductor - AL Str Size	600 kcmil
Conductor - AL Str Size Range	600 kcmil

Certifications And Compliance

Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	1
Minimum Pack Quantity	4

Product Assets

- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YCAK391A4N_LineArt](#)
- [Sales Drawings - SD64095-01_A](#)
- [Specifications - YCAK36A2G1](#)