

## YCB2R, Al Stirrup Connector, hot-line clamp adapter with Al run and Cu bail

By Burndy  
Catalog # [YCB2R](#)



Stirrup Connector,Aluminum:4(Str.)AWG,2(Str.)AWG,2(Sol.)AWG,  
ACSR:2(6/1)AWG, 2(7/1)AWG, 4(6/1)AWG, 4(7/1)AWG

### Features

- Permanent compression hot-line clamp adapter with aluminum run and copper bail
- Accommodates any standard copper hotline clamp on bail elements
- Permits hotline tapping without arcing or chafing damage to aluminum conductor
- Installed with standard tools and dies

### Application

For Aluminum, ACSR, 6201, 5005, Compressed And Compact Conductors

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - ACSR Str Size	4 (6/1) Swan AWG;4 (7/1) Swanate AWG;3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG
Conductor - ACSR Str Size Range	4 (6/1) Swan AWG-2 (7/1) Sparate AWG
Conductor - AL Str Size	4 AWG;2 AWG
Conductor - AL Str Size Range	4 AWG-2 AWG

### Dimensions

Dimension - F Width Center to Center inch	2.50 in
Dimension - L Length Overall mm	227 mm
Dimension - Height inch	3.75 in
Dimension - Height mm	95.3 mm
Dimension - Width inch	0.72 in
Dimension - Width mm	18 mm
Dimension - Bail Size	0.25 in
Dimension - Length Overall inch	8.95 in
Dimension - D inch	2.50 in

### General

Die Index	BG
Prefilled Oxide Inhibitor	N
Sub Brand	CRIMPIT
Plated	N
Type	Stirrups
UPC 12 Digit	781810151501
UPC 14 Digit GTIN	00781810151501
Material	Aluminum
Material - Bail	Copper
Plating Type	Unplated
UPC	781810151501

### Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	3000

### Product Assets

[Catalog \[English\]](#)