

By Burndy  
 Catalog # [YCB33R](#)

Stirrup Connector, Aluminum: 397.5 kcmil-400 kcmil,  
 ACSR: 336.4(26/7) kcmil, 336.4(30/7) kcmil, 397.5(18/1) kcmil



### Specifications

Standards - RoHS Compliance Status	CM
UL Listed	No

### Conductor

Conductor - ACSR Str Size	336.4 (26/7) Linnet kcmil; 336.4 (30/7) Oriole kcmil; 397.5 (18/1) Chickadee kcmil
Conductor - ACSR Str Size Range	336.4 (26/7) Linnet kcmil-397.5 (18/1) Chickadee kcmil
Conductor - AL Str Size	397 kcmil; 400 kcmil
Conductor - AL Str Size Range	397 kcmil - 400 kcmil

### Dimensions

Dimension - Width inch	1.31 in
Dimension - Width mm	33 mm
Dimension - F Width Center to Center inch	3.50 in
Dimension - Bail Size	0.324 in

Dimension - Height inch	5.39 in
Dimension - Height mm	136.5 mm
Dimension - D inch	3.50 in

### General

Die Index	M
Type	Stirrups
Prefilled Oxide Inhibitor	N
UPC 12 Digit	781810152768
UPC 14 Digit GTIN	00781810152768
Material	Aluminum
Material - Bail	Copper
UPC	781810152768

### Logistics

Minimum Pack Quantity	6
Carton Quantity	10

### Product Assets

[Catalog \[English\]](#)