

YCS28, Copper Loop Splice

By Burndy
Catalog # YCS28



CU loop splice connector designed to withstand jumper loop tensile and vibration stresses up to 60 percentage RBS, 3-1/8 IN L

Features

- Copper Loop Splice
- Designed to withstand jumper loop tensile and vibration stress up to 60 percent of Rated Breaking Strength

Application

For Copper Conductors

Specifications

| | |
|------------------------------------|----------------------|
| Buy American Compliant | Contact Manufacturer |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Buy America(n) Qualified | Contact Manufacturer |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

Conductor

| | |
|-----------------------------------|---------|
| Conductor - Copper Str Size | 4/0 AWG |
| Conductor - Copper Str Size Range | 4/0 AWG |

Configuration

| | |
|--|--------|
| Physical Attribute - Number of Crimps Required | 3 |
| Connector Type | Splice |

Dimensions

| | |
|--------------------------------|-----------|
| Dimension - L Length Overall | 78 mm |
| Dimension - A Outside Diameter | 0.89 inch |
| Dimension - B Length fraction | 1-8/17 in |
| Dimension - B Outside Diameter | 0.89 inch |
| Dimension - B Length | 1.47 inch |
| Dimension - Length Overall | 3.09 inch |

General

| | |
|---------------------------|----------------|
| Die Index | 168 |
| Trade Name | HYSPLICE™ |
| Prefilled Oxide Inhibitor | N |
| Sub Brand | HYSPLICE |
| Plated | N |
| Type | YCS |
| UPC 12 Digit | 781810014219 |
| UPC 14 Digit GTIN | 00781810014219 |
| Material | Copper |
| Plating Type | Unplated |
| UPC | 781810014219 |

Logistics

| | |
|-----------------------|------|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 25 |
| Pallet Quantity | 5800 |

Product Assets

[Catalog \[English\]](#)