



# YDS25, Copper Single Sleeve Splice

By Burndy  
Catalog # [YDS25](#)



HYSPLICE Single Sleeve Full Tension Splice, Accommodates Wire: 1/0 Cu STR (Hard, Medium, or Soft Drawn), Die Index: 165, Made of copper tubing, Installed with standard tools and dies.

## Application

For Stranded Copper Conductors

## General

Catalog Number	YDS25
Connector Type	Splice
Die Index	165
EU RoHS Indicator	Yes
Material	Copper
Oxide Inhibitor Type	Penetrox E
Physical Attribute - Number of Crimps Required	6
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810564820

## Dimensions

Dimension - B Length fraction	2-3/5 in
Dimension - B Length inch	2.59 in
Dimension - L Length Overall mm	137 mm
Dimension - Length Overall inch	5.38 in
Dimension - Outside Diameter inch	0.63 in

## Conductor Related

Conductor - Copper Str Size 1/0 AWG

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	4900

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Catalogs - Section H - Overhead Distribution](#)  
[Customer Notices - Prop 65 Notice](#)  
[Product Cross Section Image\(s\) - BUR\\_YDS\\_LineArt](#)  
[Sales Drawings - 50115709](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-YDS25-SPEC-EN | REV 6/2024