

YDS26, Copper Full Tension Sleeve

By Burndy
Catalog # [YDS26](#)



Hysplice, 2/0 (7, 12, 19) str., 6 in L, Full Tension Sleeve for Stranded Copper Conductors.

Application

For Stranded Copper Conductors

General

Catalog Number	YDS26
Connector Type	Splice
Die Index	166
EU RoHS Indicator	Yes
Material	Copper
Oxide Inhibitor Type	Penetrox E
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810564844

Dimensions

Dimension - A Outside Diameter inch	0.71 in
Dimension - B Length fraction	2-17/20 in
Dimension - B Length inch	2.85 in
Dimension - B Outside Diameter inch	0.71 in
Dimension - L Length Overall mm	151 mm
Dimension - Length Overall inch	5.95 in
Dimension - Outside Diameter inch	0.71 in

Conductor Related

Conductor - Copper Str Size 2/0 AWG

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	4350

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Catalogs - Section H - Overhead Distribution](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_YDS_LineArt](#)
[Sales Drawings - SD..015142-01](#)