

YDS27, Copper Single Sleeve Full Tension Splice



By Burndy
Catalog # [YDS27](#)

CU Full Tension Splice, Accommodates Wire: 3/0 Cu STR (Hard, Medium, or Soft Drawn), Die Index: 167

Features

- Copper Single Sleeve Full Tension Splice
- Full Rated Breaking Strength of Hard, Medium, or Soft Drawn Solid Copper Conductor

Application

For Stranded Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Str Size	3/0 AWG
-----------------------------	---------

Configuration

Physical Attribute - Number of Crimps Required	7
Connector Type	Splice

Dimensions

Dimension - B Length fraction	3-2/7 in
Dimension - B Length inch	3.29 in
Dimension - Outside Diameter inch	0.79 in
Dimension - L Length Overall mm	173 mm
Dimension - Length Overall inch	6.83 in

General

Sub Brand	HYSPLICE
Die Index	167
Trade Name	HYSPLICE™
Plated	N
Type	YDS
Prefilled Oxide Inhibitor	Y
UPC 14 Digit GTIN	00781810014639
Material	Copper
Plating Type	Unplated
UPC	781810014639
Oxide Inhibitor Type	Penetrox E

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	2450

Product Assets

[Catalog \[English\]](#)