

YDS28, Copper Single Sleeve Full Tension Splice



By Burndy
Catalog # [YDS28](#)

CU Full Tension Splice, Accommodates Wire: 4/0 Cu STR (Hard, Medium, or Soft Drawn), Die Index: 168

Features

- Copper Single Sleeve Full Tension Splice
- Full Rated Breaking Strength of Hard, Medium, or Soft Drawn Solid Copper Conductor

Application

For Stranded Copper Conductors

Specifications

| | |
|------------------------------------|----------------------|
| Buy American Compliant | Contact Manufacturer |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |
| Buy America(n) Qualified | Contact Manufacturer |

Conductor

| | |
|-----------------------------|---------|
| Conductor - Copper Str Size | 4/0 AWG |
|-----------------------------|---------|

Configuration

| | |
|--|--------|
| Physical Attribute - Number of Crimps Required | 3 |
| Connector Type | Splice |

Dimensions

| | |
|-----------------------------------|---------|
| Dimension - B Length inch | 3.27 in |
| Dimension - Outside Diameter inch | 0.89 in |
| Dimension - L Length Overall mm | 176 mm |
| Dimension - Length Overall inch | 6.91 in |

General

| | |
|---------------------------|----------------|
| Sub Brand | HYSPLICE |
| Die Index | 168 |
| Trade Name | HYSPLICE™ |
| Plated | N |
| Type | YDS |
| Prefilled Oxide Inhibitor | Y |
| UPC 14 Digit GTIN | 00781810821015 |
| Material | Copper |
| Plating Type | Unplated |
| UPC | 781810821015 |
| Oxide Inhibitor Type | Penetrox E |

Logistics

| | |
|-----------------------|------|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 20 |
| Pallet Quantity | 1960 |

Product Assets

[Catalog \[English\]](#)