



YDS34, Copper Single Sleeve Full Tension Splice

By Burndy
Catalog # [YDS34](#)



HYSPLICE Single Sleeve Full Tension Splice, Accommodates Wire: 500 kcmil Cu (Hard, Medium, or Soft Drawn), Die Index: 210, Made of copper tubing, Installed with standard tools and dies.

Application

For Stranded Copper Conductors

General

Catalog Number	YDS34
Connector Type	Splice
Die Index	210
EU RoHS Indicator	Yes
Material	Copper
Oxide Inhibitor Type	Penetrox E
Physical Attribute - Number of Crimps Required	5
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810014677

Dimensions

Dimension - B Length fraction	5-3/4 in
Dimension - B Length inch	5.75 in
Dimension - L Length Overall mm	295 mm
Dimension - Length Overall inch	11.62 in
Dimension - Outside Diameter inch	1.38 in

Conductor Related

Conductor - Copper Str Size 500 kcmil

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	5
Minimum Pack Quantity	1
Pallet Quantity	585

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Catalogs - Section H - Overhead Distribution](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_YDS_LineArt](#)
[Sales Drawings - 50115709](#)



A proud member of the Hubbell Family.