

YE28LH128, Compression Terminal Plug, Oil/Water Tight with Shroud, 4/0 Str

By Burndy

Catalog # [YE28LH128](#)



Oil and water-tight terminal with shrouded, tin-plated, CU barrel and brazed plug Used for terminating insulated CU conductor at cutout or transformer, 11.63 IN L.

Features

- Oil and water-tight terminal with shroud, tin-plated copper barrel and brazed plug
- For terminating insulated copper conductor at cutout or transformer

Application

Wire Termination

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer No
EU RoHS Indicator	Contact Manufacturer
Certification - UL Recognized	No
Buy America(n) Qualified Certification - ETL	Contact Manufacturer No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Material	COPPER
Conductor - Copper Str Size	4/0 AWG
Conductor - Copper Str Compact Size	4/0 AWG
Conductor Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG
Conductor Type	CODE

Configuration

Connector Type	INLINE PIN
----------------	------------

Current

Voltage - Maximum	35000
-------------------	-------

Dimensions

Dimension - L Length Overall mm	292 mm
Dimension - P inch	8.06 in
Dimension - B Length fraction	2-15/16 in
Dimension - B Length inch	2.92 in
Dimension - Inside Diameter inch	1.24 in
Dimension - Length BB inch	1.00 in
Dimension - Length Overall inch	11.50 in

General

Die Index	BG
Trade Name	HYSEALPLUG™
Insulation	Y
Sub Brand	HYSEALPLUG
Plated	Y
Feature - Barrel Style	Shrouded
Type	Shrouded Pin Terminals
UPC 12 Digit	781810023396
UPC 14 Digit GTIN	00781810023396
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810023396

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	3150

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)