

## YE34LH120, Compression Terminal Plug, Oil/Water Tight with Shroud

By Burndy  
Catalog # [YE34LH120](#)



Oil and water-tight terminal with shrouded, tin-plated, CU barrel and brazed plug Used for terminating insulated CU conductor at cutout or transformer, 13.25 IN L, Shroud inside dia: 1.88.

### Features

- Oil and water-tight terminal with shroud, tin-plated copper barrel and brazed plug
- For terminating insulated copper conductor at cutout or transformer

### Application

Wire Termination

### Specifications

Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - Material	COPPER
Conductor - Copper Str Size	500 KCMIL
Conductor Size	500 KCMIL
Conductor - Copper Str Size Range	500 kcmil
Conductor Type	CODE/FLEX

### Configuration

Connector Type	INLINE PIN
----------------	------------

### Current

Voltage - Maximum	35000
-------------------	-------

### Dimensions

Dimension - L Length Overall mm	337 mm
Dimension - P inch	8.06 in
Dimension - B Length fraction	3-3/4 in
Dimension - B Length inch	3.76 in
Dimension - Inside Diameter inch	1.88 in
Dimension - Length BB inch	1.50 in
Dimension - Length Overall inch	13.25 in

### General

Die Index	20
Trade Name	HYSEALPLUG™
Insulation	Y
Sub Brand	HYPLUG
Plated	Y
Feature - Barrel Style	Shrouded
Type	Shrouded Pin Terminals
UPC 12 Digit	781810023426
UPC 14 Digit GTIN	00781810023426
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810023426

### Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	1800

### Operational

Temperature Rating	194
--------------------	-----

### Product Assets

[Catalog \[English\]](#)