


## YG14B2TC2C2C Compression Bus Bar Connector

By Burndy  
 Catalog # [YG14B2TC2C2C](#)

Copper Compression Bus Bar Connector, #2 AWG SOL and/or #2 AWG SOL/STR to 1/4 " Copper Busbar



### Features

- Compression Busbar Connector
- Easier to use than Exothermic Connections
- Ideally suited for cellular tower applications.

### Application

For Direct Barial And Cellular Tower Applicatons And Is Easier To Use Than Exothermic Connections

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	Yes
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467;UL 486A;CSA C22.2 No 65
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Solid Size A	2 AWG
Conductor - Copper Solid Size A Range	2 AWG
Conductor - Copper Solid Size B	2 AWG
Conductor - Copper Solid Size B Range	2 AWG
Conductor - Copper Str Size A	2 AWG

Conductor - Copper Str Size A Range	2 AWG
Conductor Type	CU C Str-Size;CU C Solid-Size;Bar-Size

### Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

### Dimensions

Dimension - B Length fraction	64/79 in
Dimension - B Length inch	0.81 in
Dimension - Bus Bar Size Tap Side inch	1/4" Thick Busbar

### General

Trade Name	HYGROUND®
Prefilled Oxide Inhibitor	Y
Sub Brand	HYGROUND
Plated	N
Type	YG-B
UPC 12 Digit	781810232712
UPC 14 Digit GTIN	00781810232712
Material	Copper Alloy
Plating Type	Unplated
UPC	781810232712

### Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	6960

### Product Assets

[Catalog \[English\]](#)