



YG14B2TC2C6C Compression Bus Bar Connector

By Burndy

Catalog # [YG14B2TC2C6C](#)

Copper Compression Bus Bar Connector, #6 Str/Sol and/or #2 Str/Sol to 1/4" Copper Busbar



Features

- Compression Busbar Connector
- Easier to use than exothermic connections
- Ideally suited for cellular tower applications
- High conductivity wrought copper connector for attaching ground conductor to ground bus with just one crimp when using BURNDY 750 Series of compression installation tools and U1105 die set (tool and die sold separately)
- Exclusive design allows for attachment of #2 AWG Sol/Str and/or #6Sol/Str copper conductor to 1/4" thick copper busbar
- Suitable for use on 1 or 2 conductors for power, grounding and bonding applications
- UL Listed to both UL486 and UL467 (Suitable for Direct Burial) ensures this connector meets the rigors or either application
- Prefilled with PENETROX E oxide inhibitor compound and strip sealed

Application

For Direct Burial And Cellular Tower Applicatons And Is Easier To Use Than Exothermic Connections

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	Yes
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL467;UL 486A;CSA C22.2 No 65
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL467;UL 486A;CSA C22.2 No 65
Certification - CSA Approved	CM
UL Listed	No
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Solid Size	6 AWG
A	

Conductor - Copper Solid Size	6 AWG
A Range	
Conductor - Copper Solid Size	2 AWG
B	
Conductor - Copper Solid Size	6 AWG
B Range	
Conductor - Copper Str Size A	6 AWG
Conductor - Copper Str Size A	6 AWG
Range	
Conductor - Copper Str Size B	2 AWG
Conductor - Copper Str Size B	2 AWG
Range	
Conductor Type	CU C Str-Size;CU C Solid-Size;Bar-Size

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - B Length fraction	64/79 in
Dimension - B Length inch	0.81 in
Dimension - Bus Bar Size Tap Side inch	1/4" Thick Busbar

General

Trade Name	HYGROUND®
Prefilled Oxide Inhibitor	Y
Sub Brand	HYGROUND
Plated	N
Type	YG-B
UPC 12 Digit	781810199206
UPC 14 Digit GTIN	00781810199206
Material	Copper Alloy
Plating Type	Unplated
UPC	781810199206

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	4640

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YG14B2TC2C6C-SPEC-EN | REV 11/2025