



YGA2C2N Compression Grounding Lug, #2 Str Cu, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # [YGA2C2N](#)

HYLUG™ Copper Compression Terminal for Grounding; 2-Hole



Features

- Irreversible Compression Grounding Lug
- Inspection port to ensure proper cable insertion
- UL 467 Listed, acceptable for direct burial in earth or concrete
- Prefilled with PENETROX Oxide Inhibiting Compound and strip sealed
- 2 Stud Holes, 1/2" Holes, 1-3/4" Spacing
- Die Index: 10

Application

For Grounding Applications And Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	2 Str.
Conductor - Copper Str Size Range	2 AWG
Conductor Type	CU C Solid-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Terminal

Dimensions

Dimension - Outside Diameter inch	0.42 in
Dimension - L Length Overall mm	120 mm
Dimension - Pad Width inch	0.83 in
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Strip Length inch	1-5/16
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Width fraction	2/5 in
Dimension - Width inch	0.41 in
Dimension - B Length fraction	1-2/9 in
Dimension - B Length inch	1.22 in
Dimension - Bolt Hole Size inch	0.52 in
Dimension - Bolt Size inch	0.50 in
Dimension - Length Overall inch	4.71 in
Dimension - N inch	0.62 in

General

Die Index	10
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Brown
Plated	N
Type	Terminals
UPC 12 Digit	781810220306
UPC 14 Digit GTIN	00781810220306
Material	Copper
Plating Type	Unplated
UPC	781810220306

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	24000

Product Assets

[Catalog \[English\]](#)