

YGA6CTC14 Compression Grounding Lug, #6 AWG Cu, 1-Hole, 1/4" Stud

By Burndy
Catalog # [YGA6CTC14](#)



HYLUG™ Copper Compression Terminal for Grounding; 1-Hole

Features

- Irreversible compression ground terminal specifically designed for grounding applications
- Each connector has an inspection probe hole to ensure proper cable insertion
- UL467 Listed
- Acceptable for Direct Burial in earth or concrete
- UL486A Listed
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth Or Concrete, Grounding Applications

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 467;Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;UL468A-468B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	6 Sol./6 Str.
Conductor - Copper Solid Size	6
Conductor - Copper Solid Size Range	6
Conductor - Copper Str Size Range	6 Sol / 6 AWG
Conductor Type	CU C Solid-Size;CU C Str-Size

Configuration

Connector Type Terminal

Dimensions

Dimension - Outside Diameter inch	0.29 in
Dimension - L Length Overall mm	51 mm
Dimension - Pad Width inch	0.45 in
Dimension - Hole Size inch	0.27 in
Dimension - Hole Size mm	7 mm
Dimension - Strip Length inch	1 in
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/4
Dimension - B Length fraction	1-1/8 in
Dimension - B Length inch	1.12 in
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size inch	0.25 in
Dimension - Length Overall inch	2.02 in
Dimension - N inch	0.31 in

General

Die Index	7;374
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Blue
Plated	N
Type	Terminals
UPC 12 Digit	781810102466
UPC 14 Digit GTIN	00781810102466
Material	Copper
Plating Type	Unplated
UPC	781810102466

Logistics

Minimum Pack Quantity	1
Carton Quantity	100

Product Assets

[Catalog \[English\]](#)