

YGC6C8 Compression C-Crimp Connector, #6 AWG Run, #8 AWG Tap

By Burndy
Catalog # [YGC6C8](#)



Copper Compression C Tap, 6 AWG(Run)/8 AWG(Tap)

Features

- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ E2 oxide inhibiting compound

Specifications

Certification - cULus	No
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Industry Standard(s)	UL467
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Solid Run	6 AWG
Conductor - Copper Solid Run Range	6 AWG
Conductor - Copper Solid Tap	8 AWG
Conductor - Copper Solid Tap Range	8 AWG
Conductor - Copper Str Run	6 AWG
Conductor - Copper Str Run Range	6 AWG
Conductor - Copper Str Tap	8 AWG
Conductor - Copper Str Tap Range	8 AWG

Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Tap

Dimensions

Dimension - L Length Overall	16 mm
Dimension - Height fraction	46/63 in
Dimension - Height inch	0.73 in
Dimension - Height mm	18.5 mm
Dimension - Length Overall	0.62 in

General

Die Index	BG
Trade Name	CRIMPIT™
Plated	N
Type	Taps
UPC 12 Digit	781810102596
UPC 14 Digit GTIN	00781810102596
Material	Copper
Plating Type	Unplated
UPC	781810102596

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	46400

Product Assets

[Catalog \[English\]](#)