

YGHC26C2 Compression Grounding C-TAP Connector, 1-2/0 AWG Str, 3/8" Rod Run, #6 AWG Sol-#2 AWG Str Tap

By Burndy

Catalog # [YGHC26C2](#)

HYGROUND® Compression Grounding C TAP; 1-2/0 TO 6-2 Copper



Features

- Irreversible compression ground tap figure C connector
- C-shaped opening permits placing two continuous parallel cables into conductor groove
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial Cables

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837;IEEE 837 2014 Qualified;UL468A-468B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Run	3/8 in
Conductor - Rod Run Range	3/8 in
Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Solid Tap Range	6 AWG-2 AWG
Conductor - Copper Str Run	1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Run Range	1 AWG-2/0 AWG
Conductor - Copper Str Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Str Tap Range 6 AWG-2 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - L Length Overall mm	19 mm
Dimension - Height fraction	1-25/61 in
Dimension - Height inch	1.41 in
Dimension - Height mm	35.8 mm
Dimension - B Length inch	0.75 in
Dimension - Length Overall inch	0.75 in

General

Die Index	O
Trade Name	HYTAP™
Sub Brand	HYGROUND, HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810221020
UPC 14 Digit GTIN	00781810221020
Material	Copper
Plating Type	Unplated
UPC	781810221020

Logistics

Minimum Pack Quantity	1
Carton Quantity	75
Pallet Quantity	14800

Product Assets

[Catalog \[English\]](#)