

YGHC34C29 Compression Grounding C-TAP Connector

By Burndy
Catalog # [YGHC34C29](#)

Copper Compression C Connector, 300-500 kcmil (Run) & 3/0 AWG(Str) - 250 kcmil (Tap)



Features

- Irreversible compression ground tap figure C connector
- C-shaped opening permits placing two continuous parallel cables into conductor groove
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial Cables

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837;UL468A-468B
Standards - RoHS Compliance Status	CM
Industry Standard(s)	Direct Burial
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Run	300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Run Range	300 kcmil-500 kcmil
Conductor - Copper Str Tap	3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Tap Range	3/0 AWG-250 kcmil

Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Tap

Dimensions

Dimension - B Length inch	0.88 in
Dimension - L Length Overall mm	22 mm
Dimension - Height fraction	2-2/3 in
Dimension - Height inch	2.67 in
Dimension - Height mm	67.8 mm
Dimension - Length Overall inch	0.88 in

General

Sub Brand	HYGROUND, HYTAP
Die Index	1011
Trade Name	HYTAP™
Plated	N
Type	Taps
UPC 12 Digit	781810221075
UPC 14 Digit GTIN	00781810221075
Material	Copper
Plating Type	Unplated
UPC	781810221075

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalog \[English\]](#)