

YGHP29C26 Figure 6 Compression Grounding Connector, 1/0 Str-250 kcmil, 1/2"-5/8" Rod Run, 1/0-2/0 Str Tap

By Burndy
Catalog # YGHP29C26

Cu Compression Ground Rod Connector, 1/0 str- 250 kcmil , 1/2 " -5/8 " Rod (Run) to 1/0 str to 2/0 str (Tap)



Features

- Irreversible compression ground tap can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth And Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Run	3 ;4
Conductor - Rebar Run Range	3 -4
Conductor - Rod Run	1/2 in;5/8 in
Conductor - Rod Run Range	1/2 in-5/8 in
Conductor - Copper Str Run	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Run Range	1/0 -250 kcmil

Conductor - Copper Str Tap	1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	1/0 -2/0 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.75 in

General

Die Index	997
Trade Name	HYTAP™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810220931
UPC 14 Digit GTIN	00781810220931
Material	Copper
Plating Type	Unplated
UPC	781810220931

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	7350

Product Assets

[Catalog \[English\]](#)