


YGHP29C6W6W Figure 6 Compression Grounding Connector, 1/2"-5/8" Rod Run, #8 Sol-#6 Str Tap

By Burndy
Catalog # [YGHP29C6W6W](#)

High Strength Copper Irreversible Compression- Cable to cable,
Cable to ground rod, Cable to rebar



Features

- Irreversible compression ground tap figure 6 can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth And Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Run	3 ;4
Conductor - Rebar Run Range	3 -4
Conductor - Rod Size	1/2 in;5/8 in
Conductor - Rod Size Range	1/2 in-5/8 in
Conductor - Copper Solid Tap	8 AWG;7 AWG;6 AWG;5 AWG
Conductor - Copper Solid Tap Range	8 AWG-5 AWG
Conductor - Copper Str Run	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Run Range	1/0 -250 kcmil

Conductor - Copper Str Tap	8 AWG;7 AWG;6 AWG;5 AWG
Conductor - Copper Str Tap Range	8 AWG-5 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.75 in

General

Die Index	997
Trade Name	HYTAP™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810085295
UPC 14 Digit GTIN	00781810085295
Material	Copper
Plating Type	Unplated
UPC	781810085295

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	7250

Product Assets

[Catalog \[English\]](#)