

YGHP34C2 Figure 6 Compression Grounding Connector, #4 Sol-#2 Str, 5/8"-3/4" Rod

By Burndy
Catalog # [YGHP34C2](#)

High Strength Copper Irreversible Compression Ground Rod Tap Connector



Features

- Irreversible compression ground tap can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth And Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837;IEEE 837 2014 Qualified
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Run	5 ;6
Conductor - Rebar Run Range	5 -6
Conductor - Rod Run	5/8 in;3/4 in
Conductor - Rod Run Range	5/8 in-3/4 in
Conductor - Copper Solid Tap	4 AWG;3 AWG;2 AWG
Conductor - Copper Solid Tap Range	4 AWG-2 AWG
Conductor - Copper Str Run	250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil

Conductor - Copper Str Run Range	250 kcmil-500 kcmil
Conductor - Copper Str Tap	4 AWG;3 AWG;2 AWG
Conductor - Copper Str Tap Range	4 AWG-2 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.75 in

General

Die Index	998
Trade Name	HYTAP™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810220955
UPC 14 Digit GTIN	00781810220955
Material	Copper
Plating Type	Unplated
UPC	781810220955

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	4625

Product Assets

[Catalog \[English\]](#)