

YGHP34C26 Figure 6 Compression Grounding Connector, 250-500 kcmil, 5/8"-3/4" Rod, 5/8"-3/4" Rebar Run, 1/0 Str-2/0 Str Tap



By Burndy

Catalog # [YGHP34C26](#)

Cu Compression Ground Rod Connector, 250- 500 kcmil , 5/8" to 3/4" Rod, 5/8" to 3/4" Rebar (Run) to 1/0 str to 2/0 str (Tap)

Features

- Irreversible compression ground tap can be used as a tap connector or as a tap splice connector
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth And Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Run	5 ;6
Conductor - Rebar Run Range	5 -6
Conductor - Rod Run	5/8 in;3/4 in
Conductor - Rod Run Range	5/8 in-3/4 in
Conductor - Copper Str Run	250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Run Range	250 kcmil-500 kcmil

Conductor - Copper Str Tap	1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	1/0 -2/0 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - Height mm	0 mm
Dimension - B Length fraction	3/4 in
Dimension - B Length inch	0.75 in

General

Die Index	998
Trade Name	HYTAP™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810220962
UPC 14 Digit GTIN	00781810220962
Material	Copper
Plating Type	Unplated
UPC	781810220962

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	5920

Product Assets

[Catalog \[English\]](#)