



YGHP58C2W2 Figure 6 Compression Grounding Connector, 1/2"-5/8" Rod Run, #6-#2 Sol Tap

By Burndy
Catalog # [YGHP58C2W2](#)

High Strength Copper Irreversible Compression



Features

- Tap A accepts a continuous run on tap conductor
- Tap B accepts a tap conductor only
- One connector style can be used for many applications reducing number of connectors needed in inventory
- High conductivity wrought copper extrusion, identical material to the conductor, minimizes resistance and voltage drop
- UL467 Listed
- Acceptable for direct burial in earth and concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Ground Rod, Direct Burial In Earth And Concrete

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rod Tap	1/2 in;5/8 in
Conductor - Rod Tap Range	1/2 in-5/8 in
Conductor - Copper Solid Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Solid Run Range	6 AWG-2 AWG
Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Solid Tap Range 6 AWG-2 AWG

Configuration

Physical Attribute - Number of Crimps Required	1
Connector Type	Tap

Dimensions

Dimension - Pad Width inch	0.75 in
Dimension - Height inch	1.90 in
Dimension - Height mm	48.3 mm
Dimension - Width inch	0.94 in
Dimension - Width mm	24 mm
Dimension - B Length fraction	1-9/10 in
Dimension - B Length inch	1.90 in

General

Die Index	997
Trade Name	HYTAP™
Prefilled Oxide Inhibitor	Y
Oxide Inhibitor Type	Penetrox E
Sub Brand	HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810002186
UPC 14 Digit GTIN	00781810002186
Material	Copper
Plating Type	Unplated
UPC	781810002186

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	8700

Product Assets

[Catalog \[English\]](#)