

YGHS29 Compression Grounding Splice, 250 kcmil Cu

By Burndy
Catalog # [YGHS29](#)



HYGROUND® Grounding Irreversible Compression Splice

Features

- Irreversible compression ground splices specifically designed for grounding applications
- Each conductor element has an inspection probe hole and a center stop to ensure proper cable insertion
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467;UL 486A-486B;IEEE 837
Standards - RoHS Compliance Status	CM
Industry Standard(s)	UL467;UL 486A-486B;IEEE 837
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Str Size	250 kcmil
Conductor - Copper Str Size Range	250 kcmil

Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Splice

Dimensions

Dimension - B Length fraction	1-1/6 in
Dimension - B Length inch	1.18 in
Dimension - Outside Diameter inch	0.95 in
Dimension - L Length Overall mm	66 mm
Dimension - Length Overall inch	2.59 in

General

Sub Brand	HYLINK
Die Index	18
Trade Name	HYLINK™
Plated	N
Type	Splices
UPC 12 Digit	781810220481
UPC 14 Digit GTIN	00781810220481
Material	Copper
Plating Type	Unplated
UPC	781810220481

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	5760

Product Assets

[Catalog \[English\]](#)