

YGHS34 Compression Grounding Splice, 500 kcmil Cu

By Burndy
Catalog # YGHS34



HYGROUND® Grounding Irreversible Compression Splice

Features

- Irreversible compression ground splices specifically designed for grounding applications
- Each conductor element has an inspection probe hole and a center stop to ensure proper cable insertion
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial In Earth Or Concrete

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467;UL 486A-486B;IEEE 837
Standards - RoHS Compliance Status	CM
Industry Standard(s)	UL467;UL 486A-486B;IEEE 837
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Str Size	500 kcmil
Conductor - Copper Str Size Range	500 kcmil

Configuration

Physical Attribute - Number of Crimps Required	3
Connector Type	Splice

Dimensions

Dimension - B Length fraction	1-1/2 in
Dimension - B Length inch	1.48 in
Dimension - Outside Diameter inch	1.24 in
Dimension - L Length Overall mm	81 mm
Dimension - Length Overall inch	3.19 in

General

Sub Brand	HYLINK
Die Index	22
Trade Name	HYLINK™
Plated	N
Type	Splices
UPC 12 Digit	781810220498
UPC 14 Digit GTIN	00781810220498
Material	Copper
Plating Type	Unplated
UPC	781810220498

Logistics

Minimum Pack Quantity	1
Carton Quantity	6
Pallet Quantity	2784

Product Assets

[Catalog \[English\]](#)