

## YGS28 Compression Grounding Splice, 4/0 AWG Cu

By Burndy  
Catalog # [YGS28](#)

HYGROUND® Grounding Irreversible Compression Splice



### Features

- Irreversible compression ground splices specifically designed for grounding applications
- Each conductor element has an inspection probe hole and a center stop to ensure proper cable insertion
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

### Application

For Direct Burial In Earth Or Concrete

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467;UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B;UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Str Size	4/0 Str.
Conductor - Copper Str Size Range	4/0 Str.
Conductor Type	CU C Str-Size

### Configuration

Physical Attribute - Number of Crimps Required	2
Connector Type	Splice

### Dimensions

Dimension - Outside Diameter inch	0.69 in
Dimension - L Length Overall mm	86 mm
Dimension - B Length fraction	1-7/20 in
Dimension - B Length inch	1.57 in
Physical Attribute - Tongue Angle	Straight
Dimension - Length Overall inch	3.37 in

### General

Die Index	15
Trade Name	HYLINK™
Sub Brand	HYLINK
Plated	N
Type	Splices
UPC 12 Digit	781810220429
UPC 14 Digit GTIN	00781810220429
Material	Copper
Plating Type	Unplated
UPC	781810220429

### Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	9600

### Product Assets

[Catalog \[English\]](#)