

YH2929WCC, Cu Compression H Tap and Clear Cover, 250 kcmil-2 AWG Run and Tap

By Burndy

Catalog # [YH2929WCC](#)

Copper Compression H Tap, 250 kcmil-2 AWG (Main), 250 kcmil-2 AWG (Tap), Tin Plated



Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Copper Flex I Tap	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Flex I Tap Range	4/0 AWG-2 AWG
Conductor - Copper Flex K Run	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Flex K Tap	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Flex M Run	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Flex M Tap	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Flex G Run	2;1;1/0;2/0;3/0;4/0
Conductor - Copper Str Run	2;1;1/0;2/0;3/0;4/0;250
Conductor - Copper Flex G Tap	2;1;1/0;2/0;3/0;4/0

Conductor - Copper Str Run Range	250 KCMIL-2 AWG
Conductor - Copper Str Tap	2;1;1/0;2/0;3/0;4/0;250
Conductor - Copper Str Tap Range	250 KCMIL-2 AWG
Conductor - Copper Flex H Tap	2;1;1/0;2/0;3/0;4/0
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Run	4/0 AWG-2 AWG

Configuration

Connector Type	H-TAP W/CLR COVER
----------------	-------------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall	23 mm
Dimension - Strip Length inch	1-1/16
Dimension - Width inch	1.85 in
Dimension - Length Overall	0.90 in

General

Die Index	654
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Color Code	Purple
Plated	Y
Type	Compression Taps
UPC 12 Digit	781810436424
UPC 14 Digit GTIN	00781810436424
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810436424

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	900

Operational

Temperature Rating	194
--------------------	-----



A Hubbell brand