


YH2C2CWCC, Cu Compression H Tap and Clear Cover, 2-8 AWG Run and Tap

By Burndy
Catalog # [YH2C2CWCC](#)



Copper Compression H Tap, 2 AWG-8 AWG (Main), 2 AWG-8 AWG (Tap), Tin Plated

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Copper Flex I Tap	8;7;6;5;4;3;2
Conductor - Copper Flex I Tap Range	2 AWG-8 AWG
Conductor - Copper Flex K Run	8;7;6;5;4;3;2
Conductor - Copper Flex K Run Range	8 AWG
Conductor - Copper Flex K Tap	8;7;6;5;4;3;2
Conductor - Copper Flex K Tap Range	8 AWG
Conductor - Copper Flex M Run	8;7;6;5;4;3;2

Conductor - Copper Flex M Tap	8;7;6;5;4;3;2
Conductor - Copper Solid Run	6;5;4;3;2
Conductor - Copper Solid Tap	6;5;4;3;2
Conductor - Copper Flex G Run	8;7;6;5;4;3;2
Conductor - Copper Flex G Run Range	2 AWG-6 AWG
Conductor - Copper Flex G Tap	8;7;6;5;4;3;2
Conductor - Copper Str Run	2 AWG-6 AWG Range
Conductor - Copper Flex G Tap Range	2 AWG-14 AWG Range
Conductor - Copper Flex H Run	2 AWG-6 AWG Range
Conductor - Copper Str Tap	2 AWG-6 AWG Range
Conductor - Copper Flex H Tap	8;7;6;5;4;3;2
Conductor - Copper Flex H Tap Range	2 AWG-14 AWG Range
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Run	2 AWG-8 AWG

Configuration

Connector Type	H-TAP W/CLR COVER
----------------	-------------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall	19 mm
Dimension - Strip Length inch	7/8
Dimension - Width inch	1.25 in
Dimension - Length Overall	0.75 in

General

Die Index	C
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Color Code	Brown
Plated	Y
Type	Compression Taps
UPC 12 Digit	781810436455
UPC 14 Digit GTIN	00781810436455

Material COPPER
Plating Type Tin - Electro Plated
Finish Type Tin-Plated
UPC 781810436455

Pallet Quantity 825

Operational

Temperature Rating 194

Logistics

Minimum Pack Quantity 1
Carton Quantity 25

Product Assets

[Catalog \[English\]](#)



A Hubbell brand