




YH3434WCC, Compression H-Tap, Main 500-250 kcmil, Tap 500-250 kcmil, includes clear cover

By Burndy
Catalog # [YH3434WCC](#)



Copper Compression H Tap, 500 KCMIL-250 KCMIL (Main), 500 KCMIL-4/0 AWG(Tap), Tin Plated

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Copper Flex I Tap	4/0;250;300;350
Conductor - Copper Flex I Tap Range	350 KCMIL-4/0 AWG
Conductor - Copper Flex K Run	4/0;250;300;350
Conductor - Copper Flex K Tap	4/0;250;300;350
Conductor - Copper Flex M Run	4/0;250;300;350
Conductor - Copper Flex M Tap	4/0;250;300;350
Conductor - Copper Flex G Run	4/0;250;300;350
Conductor - Copper Str Run	250;300;350;400;450;500

Conductor - Copper Flex G Tap	4/0;250;300;350
Conductor - Copper Str Run Range	500 KCMIL-250 KCMIL
Conductor - Copper Str Tap	4/0;250;300;350;400;450;500
Conductor - Copper Str Tap Range	500 KCMIL-4/0 AWG
Conductor - Copper Flex H Tap	4/0;250;300;350
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Run	350 KCMIL-4/0 AWG

Configuration

Connector Type	H-TAP W/CLR COVER
----------------	-------------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall	25 mm
Dimension - Strip Length inch	1-1/8
Dimension - Width inch	2.43 in
Dimension - Length Overall	1.00 in

General

Die Index	1104
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Color Code	Brown
Plated	Y
Type	Compression Taps
UPC 12 Digit	781810436479
UPC 14 Digit GTIN	00781810436479
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810436479

Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	900



A Hubbell brand