

YHD200, Compression Line Tap, CU, AL, ACSR, Compact

By Burndy
Catalog # [YHD200](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range, groove A(Run):0.398-0.470

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Cmpt Run	2/0 AWG;3/0 AWG
Conductor - ACSR Cmpt Run Range	2/0 AWG-3/0 AWG
Conductor - ACSR Cmpt Tap	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - ACSR Cmpt Tap Range	6 AWG-1 AWG
Conductor - ACSR Str Run	1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Run Range	1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG;5 (6/1) Thrush AWG;4 (6/1) Swan AWG;4 (7/1) Swanate AWG;3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG

Conductor - ACSR Str Tap Range	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - AL Str Run	3/0 - 4/0
Conductor - AL Str Run Range	3/0 - 4/0
Conductor - AL Str Tap	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - AL Str Tap Range	6 AWG-1 AWG
Conductor - Copper Solid Run	3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG
Conductor - Copper Solid Tap Range	6 AWG-1/0 AWG
Conductor - Copper Str Run	2/0 AWG;3/0 AWG
Conductor - Copper Str Run Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - Copper Str Tap Range	6 AWG-1 AWG

Dimensions

Dimension - L Length Overall	41 mm
Dimension - Height fraction	1-11/25 in
Dimension - Height inch	1.45 in
Dimension - Height mm	36.8 mm
Dimension - Width inch	0.89 in
Dimension - Width mm	23 mm
Dimension - Length Overall	1.62 in
inch	

General

Die Index	D3
Trade Name	HYCRIMP™
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Plated	N
Type	YHD
UPC 14 Digit GTIN	00781810139158
Material	Aluminum
Plating Type	Unplated
UPC	781810139158

Logistics

Minimum Pack Quantity 25
Carton Quantity 250
Pallet Quantity 8250

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YHD200-SPEC-EN | REV 11/2025