

## YHD3, Line Tap Connector, AL-CU, AL-AL

By Burndy  
Catalog # [YHD3](#)

Compression Line Tap Connector for Aluminum to Copper and Aluminum to Aluminum applications, 1.47 H, 1.88 L, .76 W



### Features

- LOKTAP™ compression connectors are high quality, range-taking devices accommodating many combinations of conductor
- LOKTAP™ connectors feature a C groove on both sides of the connector for use in street lighting applications

### Application

For Accommodate Combinations Of Aluminum To Copper, And Aluminum To Aluminum Conductors

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - ACSR Cmpt Run	2/0 AWG;3/0 AWG
Conductor - ACSR Cmpt Run Range	2/0 AWG-3/0 AWG
Conductor - ACSR Cmpt Tap	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - ACSR Cmpt Tap Range	6 AWG-1 AWG
Conductor - ACSR Str Run	1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Run Range	1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap	6 (6/1) Turkey AWG;5 (6/1) Thrush AWG;4 (6/1) Swan AWG;4 (7/1) Swanate AWG;3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG
Conductor - ACSR Str Tap Range	6 (6/1) Turkey AWG-2 (7/1) Sparate AWG
Conductor - AL Str Run	2/0 AWG;3/0 AWG
Conductor - AL Str Run Range	2/0 AWG-3/0 AWG
Conductor - AL Str Tap	6 AWG;4 AWG;3 AWG;2 AWG

Conductor - AL Str Tap Range	6 AWG-2 AWG
Conductor - Copper Solid Run	3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Solid Tap	#6;5 AWG;4 AWG;3 AWG;2 AWG;1/0
Conductor - Copper Solid Tap Range	#6-1/0
Conductor - Copper Str Run	2/0 AWG;3/0 AWG
Conductor - Copper Str Run Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Tap Range	LOKTAP™ Compression Line Tap Connector for Aluminum to Copper and Aluminum to Aluminum applications

### Dimensions

Dimension - L Length Overall	48 mm
Dimension - Height fraction	1-47/100 in
Dimension - Height inch	1.47 in
Dimension - Height mm	37.3 mm
Dimension - Width fraction	19/25 in
Dimension - Width inch	0.76 in
Dimension - Width mm	19 mm
Dimension - Length Overall inch	1.88 in

### General

Die Index	D3
Trade Name	LOKTAP™
Prefilled Oxide Inhibitor	Y
Sub Brand	LOKTAP
Plated	N
Type	YHD
UPC 14 Digit GTIN	00781810139066
Material	Aluminum
Plating Type	Unplated
UPC	781810139066

### Logistics

Minimum Pack Quantity	25
Carton Quantity	250
Pallet Quantity	4000



A Hubbell brand