

YHD300, Line Tap, Cu, AL, ACSR, Compact

By Burndy
Catalog # YHD300

Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range- groove A(Run): 0.336 - 0.470



Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Cmpt Run	1/0 AWG;2/0 AWG
Conductor - ACSR Cmpt Run Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	1/0 AWG;2/0 AWG;3/0 AWG
Conductor - ACSR Cmpt Tap Range	1/0 AWG-3/0 AWG
Conductor - ACSR Str Run	1 (6/1) Robin AWG;1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Run Range	1 (6/1) Robin AWG-2/0 (6/1) Quail AWG

Conductor - ACSR Str Tap	1 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap Range	1 (6/1) Raven AWG-2/0 (6/1) Quail AWG
Conductor - AL Str Run	2/0 - 4/0
Conductor - AL Str Run Range	2/0 - 4/0
Conductor - AL Str Tap	1 AWG;1/0 AWG;2/0 AWG
Conductor - AL Str Tap Range	1 AWG-2/0 AWG
Conductor - Copper Solid Run	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	2/0 AWG-4/0 AWG
Conductor - Copper Solid Tap	2/0 AWG;3/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Run	#1(3);2 AWG;1 AWG;1/0 ;2/0 AWG;3/0
Conductor - Copper Str Run Range	#1(3)-3/0
Conductor - Copper Str Tap	2/0 AWG;3/0 AWG
Conductor - Copper Str Tap Range	2/0 AWG-3/0 AWG

Dimensions

Dimension - L Length Overall	41 mm
Dimension - Height fraction	1-21/50 in
Dimension - Height inch	1.42 in
Dimension - Height mm	36.1 mm
Dimension - Width fraction	89/100 in
Dimension - Width inch	0.89 in
Dimension - Width mm	23 mm
Dimension - Length Overall	1.62 in
inch	

General

Die Index	D3
Trade Name	HYCRIMP™
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Plated	N
Type	YHD
UPC 14 Digit GTIN	00781810139257
Material	Aluminum
Plating Type	Unplated
UPC	781810139257

Logistics

Minimum Pack Quantity	25
Carton Quantity	250

Pallet Quantity

8250

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YHD300-SPEC-EN | REV 11/2025