

## YHD350, Line Tap Connector, AL-CU, AL-AL

By Burndy  
Catalog # [YHD350](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, wire diameter range, groove A(Run):0.461-0.563

### Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

### Application

For Copper, Aluminum Or ACSR And Compact Conductors

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - ACSR Cmpt Run	1/0 AWG;2/0 AWG
Conductor - ACSR Cmpt Run Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	1 AWG;1/0 AWG;3/0 AWG;2/0 AWG
Conductor - ACSR Cmpt Tap Range	1 AWG-2/0 AWG
Conductor - ACSR Str Run	3/0 (6/1) Pigeon AWG;4/0 (6/1) Penguin AWG
Conductor - ACSR Str Run Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penguin AWG
Conductor - ACSR Str Tap	1 (6/1) Robin AWG;1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap Range	1 (6/1) Robin AWG-2/0 (6/1) Quail AWG
Conductor - AL Str Run	3/0-4/0
Conductor - AL Str Run Range	3/0-4/0

Conductor - AL Str Tap	2/0 AWG;3/0 AWG
Conductor - AL Str Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Solid Run	250 - 300
Conductor - Copper Solid Run Range	250 - 300
Conductor - Copper Solid Tap	2/0 AWG;3/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Run	3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Tap	1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	1 AWG-2/0 AWG

### Dimensions

Dimension - L Length Overall	57 mm
Dimension - Height fraction	1-21/50 in
Dimension - Height inch	1.42 in
Dimension - Height mm	36.1 mm
Dimension - Width fraction	89/100 in
Dimension - Width inch	0.89 in
Dimension - Width mm	23 mm
Dimension - Length Overall	2.25 in
inch	

### General

Die Index	D3
Trade Name	HYCRIMP™
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Plated	N
Type	YHD
UPC 14 Digit GTIN	00781810139301
Material	Aluminum
Plating Type	Unplated
UPC	781810139301

### Logistics

Minimum Pack Quantity	25
Carton Quantity	200
Pallet Quantity	3200



A Hubbell brand