



## YHN600, Line Tap for CU, AL, ACSR, Compact

By Burndy  
Catalog # [YHN600](#)

Compression Line Tap for Copper, AL or ACSR and Compact  
Conductors, wire diameter range, groove A(Run):0.57-0.81.



## General

Catalog Number	YHN600
Die Index	N
Material	Aluminum
Prefilled Oxide Inhibitor	Y
Trade Name	HYCRIMP™
UPC	781810139608
UPC 14 Digit GTIN	00781810139608

## Dimensions

Dimension - Height fraction	2 in
Dimension - Height inch	2.00 in
Dimension - Height mm	50.8 mm
Dimension - Width fraction	1-7/25 in
Dimension - Width inch	1.28 in
Dimension - Width mm	33 mm

## Conductor Related

Conductor - ACSR Cmpt Run	300 kcmil;556.5 kcmil
Conductor - ACSR Cmpt Run Range	300 kcmil-556.5 kcmil
Conductor - ACSR Cmpt Tap	300 kcmil;397 kcmil
Conductor - ACSR Cmpt Tap Range	300 kcmil-397 kcmil
Conductor - ACSR Str Run	266.8 (18/1) Waxwing kcmil;266.8 (26/7) Owl kcmil;266.8 (26/7) Partridge kcmil;300.0 (26/7) Ostrich kcmil;336.4 (18/1) Merlin kcmil;336.4 (26/7) Linnet kcmil;336.4 (30/7) Oriole kcmil;397.5 (18/1) Chickadee kcmil;397.5 (24/7) Brant kcmil;397.5 (26/7) Ibis kcmil;397.5 (30/7) Larkspur kcmil;477.0 (18/1) Pelican kcmil
Conductor - ACSR Str Run Range	266.8 (18/1) Waxwing kcmil-477.0 (18/1) Pelican kcmil
Conductor - ACSR Str Tap	266.8 (18/1) Waxwing kcmil;300.0 (26/7) Ostrich kcmil;266.8 (26/7) Owl kcmil;266.8 (26/7) Partridge kcmil;336.4 (18/1) Merlin kcmil

Conductor - ACSR Str Tap Range	266.8 (18/1) Waxwing kcmil-336.4 (18/1) Merlin kcmil
Conductor - AL Str Run	250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil
Conductor - AL Str Run Range	250 kcmil-500 kcmil
Conductor - AL Str Tap	250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil
Conductor - AL Str Tap Range	250 kcmil-350 kcmil
Conductor - Copper Solid Tap	336-400
Conductor - Copper Solid Tap Range	336-400
Conductor - Copper Str Run	250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Run Range	250 kcmil-500 kcmil
Conductor - Copper Str Tap	250 - 350
Conductor - Copper Str Tap Range	250 - 350

## Certifications And Compliance

Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	50
Minimum Pack Quantity	50

## Product Assets

- [3D Models - YHN600\\_MODEL-STEP](#)
- [3D Models - YHN600\\_MODEL-PDF](#)
- [3D Models - YHN600\\_MODEL-IGES](#)
- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_YH\\_LINEART](#)
- [Sales Drawings - SD..073376-01](#)
- [Specifications - YHN600](#)