


# YHR900, Line Tap for Cu, AL, ACSR, Compact

By Burndy  
Catalog # [YHR900](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, groove A(Run) ACSR:556.5 (18/1) - 795 (26/7)

## Features

- Wide range, universal and reversible Figure H-Shaped aluminum connector
- Conductors are separated by the shape of the connector
- Bendable tabs secure both run and tap conductors freeing the installer to work with the installation tool
- Massive aluminum design miniizes corrosion due to galvanic corrosion
- Prefilled with PENETROX Joint Compound and individually packaged

## Application

For Copper, Aluminum Or ACSR And Compact Conductors

## Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

## Conductor

Conductor - ACSR Cmpt Run	795 - 954
Conductor - ACSR Cmpt Run Range	795 - 954
Conductor - ACSR Cmpt Tap	795 - 954
Conductor - ACSR Cmpt Tap Range	795 - 954
Conductor - ACSR Str Run	<ul style="list-style-type: none"> <li>• 556.5 (24/7) Parakeet kcmil</li> <li>• 556.5 (26/7) Dove kcmil</li> <li>• 556.5 (30/7) Eagle kcmil</li> <li>• 605 (24/7) Peacock kcmil</li> <li>• 605 (26/7) Squab kcmil</li> <li>• 605 (30/19) Teal kcmil</li> <li>• 636 (24/7) Rook kcmil</li> <li>• 636 (26/7) Grosbeak kcmil</li> <li>• 636 (30/19) Egret kcmil</li> <li>• 666.6 (24/7) Flamingo kcmil</li> <li>• 715.5 (54/7) Crow kcmil</li> <li>• 715.5 (24/7) Stilt kcmil</li> <li>• 715.5 (26/7) Starling kcmil</li> </ul>

Conductor - ACSR Str Run Range

Conductor - ACSR Str Tap

Conductor - ACSR Str Tap Range

Conductor - AL Str Run

Conductor - AL Str Run Range

Conductor - AL Str Tap

Conductor - AL Str Tap Range

Conductor - Copper Str Run

- 715.5 (30/19) Redwing kcmil
- 795 (54/7) Condor kcmil
- 795 (26/7) Drake kcmil
- 556.5 (24/7) Parakeet kcmil-
- 795 (26/7) Drake kcmil
- 556.5 (24/7) Parakeet kcmil
- 556.5 (26/7) Dove kcmil
- 556.5 (30/7) Eagle kcmil
- 605 (24/7) Peacock kcmil
- 605 (26/7) Squab kcmil
- 605 (30/19) Teal kcmil
- 636 (24/7) Rook kcmil
- 636 (26/7) Grosbeak kcmil
- 636 (30/19) Egret kcmil
- 666.6 (24/7) Flamingo kcmil
- 715.5 (54/7) Crow kcmil
- 715.5 (24/7) Stilt kcmil
- 715.5 (26/7) Starling kcmil
- 715.5 (30/19) Redwing kcmil
- 795 (54/7) Condor kcmil
- 795 (26/7) Drake kcmil
- 556.5 (24/7) Parakeet kcmil-
- 795 (26/7) Drake kcmil
- 600 kcmil
- 636 kcmil
- 650 kcmil
- 700 kcmil
- 715 kcmil
- 750 kcmil
- 795 kcmil
- 800 kcmil
- 874 kcmil
- 900 kcmil
- 600 kcmil-900 kcmil
- 600 kcmil
- 636 kcmil
- 650 kcmil
- 700 kcmil
- 715 kcmil
- 750 kcmil
- 795 kcmil
- 800 kcmil
- 874 kcmil
- 900 kcmil
- 600 kcmil-900 kcmil
- 600 kcmil
- 700 kcmil

Conductor - Copper Str Run Range

- 750 kcmil
- 800 kcmil
- 850 kcmil
- 900 kcmil

600 kcmil-900 kcmil

Conductor - Copper Str Tap Range

- 600 kcmil
- 700 kcmil
- 750 kcmil
- 800 kcmil
- 850 kcmil
- 900 kcmil

600 kcmil-900 kcmil

Conductor - Copper Str Tap Range

600 kcmil-900 kcmil

**Dimensions**

Dimension - L Length Overall mm 117 mm

Dimension - Height fraction 2-97/100 in

Dimension - Height inch 2.97 in

Dimension - Height mm 75.4 mm

Dimension - Width fraction 1-37/50 in

Dimension - Width inch 1.74 in

Dimension - Width mm 44 mm  
 Dimension - Length Overall inch 4.62 in

**General**

Die Index KR  
 Trade Name HYCRIMP™  
 Prefilled Oxide Inhibitor Y  
 Sub Brand HYCRIMP  
 Plated N  
 Type YHR  
 UPC 14 Digit GTIN 00781810139851  
 Material Aluminum  
 Plating Type Unplated  
 UPC 781810139851

**Logistics**

Minimum Pack Quantity 10  
 Carton Quantity 10  
 Pallet Quantity 440

**Product Assets**

[Catalog \[English\]](#)



A Hubbell brand