




YP26AU2, Figure 3-shaped Aluminum Connector with adjustable spacer

By Burndy
Catalog # [YP26AU2](#)

Wide range, universal and reversible, Figure 3 shaped aluminum connector with adjustable overhanging spacer that separates conductors, Conductor Groove A Solid: 1, 1/0, 2/0, 3/0.



Features

- Wide range universal and reversible, Figure 3-shaped aluminum connector features adjustable overhanging spacer that separates conductors
- Spacer holds run or tap in place, permitting lineman to either approach the line ready to crimp or to assemble connector and tap on run and then crimp
- Massive aluminum design minimizes conductor corrosion due to galvanic action
- Pre-filled with PENETROX joint compoud and stripsealed

Application

For Copper, Aluminum Or ACSR Conductors

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - ACSR Str Size A	3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG;2 (7/1) Sparate AWG;1 (6/1) Robin AWG;1/0 (6/1) Raven AWG
Conductor - ACSR Str Size A Range	3 (6/1) Swallow AWG-1/0 (6/1) Raven AWG
Conductor - ACSR Str Size B	6 (6/1) Turkey AWG;5 (6/1) Thrush AWG;4 (6/1) Swan AWG;4 (7/1) Swanate AWG;3 (6/1) Swallow AWG;2 (6/1) Sparrow AWG
Conductor - ACSR Str Size B Range	6 (6/1) Turkey AWG-2 (6/1) Sparrow AWG
Conductor - AL Str Size A	3 AWG;2 AWG;1 AWG;1/0 AWG
Conductor - AL Str Size A Range	3 AWG-1/0 AWG
Conductor - AL Str Size B	6 AWG;4 AWG;3 AWG;2 AWG

Conductor - AL Str Size B Range	6 AWG-2 AWG
Conductor - Copper Solid Size A	1 AWG;1/0 AWG;2/0 AWG;3/0 AWG
Conductor - Copper Solid Size A Range	1 AWG-3/0 AWG
Conductor - Copper Solid Size B	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG
Conductor - Copper Solid Size B Range	1 AWG-3/0 AWG
Conductor - Copper Str Size A	2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Size A Range	2 AWG-2/0 AWG
Conductor - Copper Str Size B	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - Copper Str Size B Range	6 AWG-1 AWG

Dimensions

Dimension - Height inch	1.30 in
Dimension - Width inch	0.72 in
Dimension - Length Overall inch	1.50 in

General

Die Index	O
Trade Name	CABELOK™ CRIMPIT™
Prefilled Oxide Inhibitor	Y
Sub Brand	CABELOK CRIMPIT
Plated	N
Type	YP-U
UPC 12 Digit	781810130650
UPC 14 Digit GTIN	00781810130650
Material	Aluminum
Plating Type	Unplated
UPC	781810130650

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	5000

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YP26AU2-SPEC-EN | REV 11/2025