


YP2U3, Figure 3-shaped Aluminum Connector with adjustable spacer

By Burndy
Catalog # [YP2U3](#)



Wide range, universal and reversible, Figure 3 shaped aluminum connector with adjustable overhanging spacer that separates conductors, Conductor Groove A Solid: 6, 4, 3, 2.

Features

- Wide range universal and reversible, Figure 3-shaped aluminum connector features adjustable overhanging spacer that separates conductors
- Spacer holds run or tap in place, permitting lineman to either approach the line ready to crimp or to assemble connector and tap on run and then crimp
- Massive aluminum design minimizes conductor corrosion due to galvanic action
- Pre-filled with PENETROX joint compound and stripsealed

Application

For Copper, Aluminum Or ACSR Conductors

Specifications

| | |
|------------------------------------|-----|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | No |
| UL Listed | No |

Conductor

| | |
|-----------------------------------|---|
| Conductor - ACSR Str Size A | 6 (6/1) Turkey AWG; 5 (6/1) Thrush AWG; 4 (6/1) Swan AWG; 4 (7/1) Swanate AWG |
| Conductor - ACSR Str Size A Range | 6 (6/1) Turkey AWG-4 (7/1) Swanate AWG |
| Conductor - ACSR Str Size B | 6 (6/1) Turkey AWG; 5 (6/1) Thrush AWG; 4 (6/1) Swan AWG; 4 (7/1) Swanate AWG |
| Conductor - ACSR Str Size B Range | 6 (6/1) Turkey AWG-4 (7/1) Swanate AWG |
| Conductor - AL Str Size A | 6 AWG; 4 AWG |
| Conductor - AL Str Size A Range | 6 AWG-4 AWG |
| Conductor - AL Str Size B | 6 AWG; 4 AWG |
| Conductor - AL Str Size B Range | 6 AWG-4 AWG |

| | |
|---------------------------------------|-----------------------------------|
| Conductor - Copper Solid Size A | 6 AWG; 5 AWG; 4 AWG; 3 AWG; 2 AWG |
| Conductor - Copper Solid Size A Range | 6 AWG-2 AWG |
| Conductor - Copper Solid Size B | 6 AWG; 5 AWG; 4 AWG; 3 AWG; 2 AWG |
| Conductor - Copper Solid Size B Range | 6 AWG-2 AWG |
| Conductor - Copper Str Size A | 6 AWG; 5 AWG; 4 AWG; 3 AWG |
| Conductor - Copper Str Size A Range | 6 AWG-3 AWG |
| Conductor - Copper Str Size B | 6 AWG; 5 AWG; 4 AWG; 3 AWG |
| Conductor - Copper Str Size B Range | 6 AWG-3 AWG |

Dimensions

| | |
|------------------------------|-----------|
| Dimension - L Length Overall | 38 mm |
| Dimension - Height | 1.30 inch |
| Dimension - Width | 0.72 inch |
| Dimension - Length Overall | 1.50 inch |

General

| | |
|---------------------------|-------------------|
| Die Index | O |
| Trade Name | CABELOK™ CRIMPIT™ |
| Prefilled Oxide Inhibitor | Y |
| Sub Brand | CABELOK CRIMPIT |
| Plated | N |
| Type | YP-U |
| UPC 12 Digit | 781810131732 |
| UPC 14 Digit GTIN | 00781810131732 |
| Material | Aluminum |
| Plating Type | Unplated |
| UPC | 781810131732 |

Logistics

| | |
|-----------------------|------|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 50 |
| Pallet Quantity | 3700 |

Product Assets

[Catalog \[English\]](#)