



# Nylon Pigtail Splice For 4,205 cmils

By Burndy  
Catalog # [YQE91](#)

Brass Pigtail Splice, 14-18 AWG, 600 V, 0.76" L, Nylon Insul, Tin Plated, 1000V(for building wiring).



## Application

For Splicing A Wide Range Of Different Cable Sizes

## General

Connector Type	Pigtail
EU RoHS Indicator	Yes
Insulation	Y
Insulation Type	Nylon
Material	Copper
Plated	N
Plating Type	Tin
Sub Brand	INSULINK
Trade Name	INSULINK™
Type	YQE
UPC	781810029480
UPC 12 Digit	7818100294800

## Dimensions

Dimension - B Length fraction	3/10 in
Dimension - B Length inch	0.30 in
Dimension - L Length Overall mm	19 mm
Dimension - Length Overall inch	0.76 in
Dimension - Pad Width inch	0.24 in
Dimension - Strip Length inch	5/16

## Electrical Ratings

Voltage - Maximum	600 V
-------------------	-------

## Conductor Related

Conductor - Copper Solid Size	18 AWG;17 AWG;16 AWG;15 AWG;14 AWG
Conductor - Copper Solid Size Range	18 AWG-14 AWG
Conductor - Copper Str Size	18 AWG;16 AWG;14 AWG
Conductor - Copper Str Size Range	18 AWG-14 AWG
Conductor Size	4,205 cmils
Conductor Type	CU C Str-Size

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	1000
Pallet Quantity	99999

## Product Assets

[3D Models - YQE91\\_MODEL-IGES](#)  
[3D Models - YQE91\\_MODEL-PDF](#)  
[3D Models - YQE91\\_MODEL-STEP](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_YQE\\_LineArt](#)  
[Sales Drawings - sc035090-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY\_CA-YQE91-SPEC-EN | REV 6/2024