

YS26, Cu Compression Splice, Long Barrel, 2/0 AWG

By Burndy
Catalog # [YS26](#)



2/0 AWG, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	<ul style="list-style-type: none"> • 700 KCMIL • 750 KCMIL
Conductor - Copper Str Size	<ul style="list-style-type: none"> • 700 KCMIL • 750 KCMIL
Conductor - Copper Str Navy Size	125 (61) Navy
Conductor Size	2/0 AWG
Conductor - Copper Str Size Range	2/0 AWG
Conductor Type	CODE

Configuration

Connector Type	LONG BARREL
----------------	-------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	84 mm
Package Height	0.000 in
Dimension - Strip Length inch	1-1/2
Dimension - B Length inch	1.45 in
Dimension - Length Overall inch	3.30 in

General

Die Index	13
Trade Name	HYLINK™
Sub Brand	HYLINK
Color Code	Black
Plated	Y
Feature - Barrel Type	Long
Feature - Barrel Style Type	Chamfered
UPC 12 Digit	781810507605
UPC 14 Digit GTIN	00781810507605
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810507605

Logistics

Minimum Pack Quantity	1
Carton Quantity	10

Product Assets

[Catalog \[English\]](#)