

YS28, Cu Compression Splice, Long Barrel, 4/0 AWG

By Burndy
Catalog # [YS28](#)



4/0 AWG, CU, Long Barrel SPLICE

Features

- Copper seamless barrel with center stop indentations to indicate when wire is fully inserted into each side of the barrel
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors clearly marked with color coding

Application

Wire Splice

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2000 KCMIL
Conductor - Copper Str Size	2000 KCMIL
Conductor - Copper Str Navy Size	200 (61) Navy
Conductor Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG
Conductor Type	CODE

Configuration

Connector Type LONG BARREL

Current

Voltage - Maximum 35000
Voltage Rating 35 kV

Dimensions

Dimension - L Length Overall mm 91 mm
Dimension - Strip Length inch 1-11/16
Dimension - B Length inch 1.58 in
Dimension - Length Overall inch 3.57 in

General

Die Index 15
Trade Name HYLINK™
Sub Brand HYLINK
Color Code Purple
Plated Y
Feature - Barrel Type Long
Feature - Barrel Style Chamfered
Type YS, Long Barrel
UPC 12 Digit 781810507803
UPC 14 Digit GTIN 00781810507803
Material COPPER
Plating Type Tin - Electro Plated
Finish Type Tin-Plated
UPC 781810507803

Logistics

Minimum Pack Quantity 1
Carton Quantity 10

Product Assets

[Catalog \[English\]](#)